
I'm not a robot



reCAPTCHA
[Privacy](#) - [Terms](#)

Continue

Driver Jbl 2426j

The mathematically determined phasing plug consists of concentric exponential horns to minimize phase cancellations.. Driver Jbl Modelo 2426j MercadolibreDriver Jbl 2426jShop our huge selection of Raw Frame Speakers and Drivers at FullCompass.. C DRIVER MODEL 2426 SPECIFICATIONS Horn Throat Exit Diameter 1" / 25mm Impedance 8 or 16 ohms Frequency Response 500 Hz - 20kHz Continuous Program Power 70 Watts above 800Hz Continuous Program Power 100 Watts above 1.. Overview The model is a professional quality high frequency compression driver which incorporates JBL's titanium diamond diaphragm.. The depth of the diamond pattern is closely controlled to provide predictable frequencies for the 2nd and 3rd normal resonance modes and for the basic suspension resonance.

75' / 44mm Voice Coil Material Edgewound Aluminum Ribbon Diaphragm Material Pure Titanium Flux Density 1.. 2kHz Minimum Cut-off Frequency 800 Hz, 12dB/octave Sensitivity (SPL) 107dB w/ JBL 2344A horn Sensitivity (SPL) 110dB w/ JBL 2370A horn Sensitivity (SPL)plane-wave tube 117dB Voice Coil Diameter 1.. com Free Shipping on Thousands of Items! JBL 2426J Compression Driver Shop for the JBL JBL 2426J 16 OHM THROAT DRIVER and receive free shipping on your order and the guaranteed lowest price.. Additionally the press-fit assembly and interlocking parts assure greater resistance to the mechanical shock.. 2 mm / 2 25' Overall Depth 4 125' / 104mm Mounting Type Bolt On *Positive voltage to BLACK terminal gives diaphragm motion toward the phasing plug* US Speaker, LLC.. JBL's exclusive suspension, consisting of a three-dimensional diamond pattern, reduces bending stresses in the diaphragm support structure.. 85 Tesla Net Weight 4 3 kg MOUNTING INFORMATION Overall Diameter 5 875' / 149 mm Hole Pattern (3) 1/4-20 threaded holes 3 Holes Equally Spaced On Diameter 57.. Diaphragm assemblies are rim centered rather than pin mounted, for instant interchangeability and ease of field service.. Driver Jbl 2426jSpecifications: • Throat Diameter: 25 mm (1 in) • Nominal Impedance: - 8 ohms2426J - 16 ohms • Minimum Impedance: 5 ohms (H), 9 ohms (J) @ 5 kHz • D.

driver movie

drivers license lyrics, drivers license, drivers license olivia rodrigo, driver movie, drivers, driver game, drivers license olivia rodrigo lyrics, driver parallel lines, drivers license song, drivers permit test, driver san francisco, driver update, driver 2, driver easy, driverpack

Through holes for external attachment points are also provided A machined ring of copper surrounds the pole piece to counteract the inductance of the voice coil at high frequencies.. All cast parts and tolerances are held to the same levels traditionally associated with JBL designs.. After manufacture, the frequency response of each driver is tested for conformity to rigid performance standards.. This titanium diamond structure combines the ruggedness of phenolic and composite-type diaphragms with the outstanding frequency response of fragile aluminum and exotic metal diaphragms.. Mounting is provided for standard 25 mm (1 in) three bolt pattern The front snout may be removed (unscrewed) to allow standard 1 3/8" - 18 screw mounting.

drivers

Driver Jbl Modelo 2426j MercadolibrePhasing plug, throat exit tube and diaphragm assemblies are identical to the previous model.. The is offered in an 8 ohm impedance, and the otherwise identical 2426J is offered in a 16 ohm impedance.

driver san francisco

e10c415e6f